

# SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

## XTeer 4T 5000 SL/MB 10W-40 (ENG)

Date of issue: 2023-03-15

Revision date: 2025-06-19

Version: 3.0

### 1. IDENTIFICATION

#### A. Product name

- XTeer 4T 5000 SL/MB 10W-40 (ENG)

#### B. Recommended use and restriction on use

- General use : Motorcycle Engine Oil
- Restriction on use : Do not use for purposes other than recommended.

#### C. Manufacturer / Supplier / Distributor information

##### Manufacturer information

- Company name : HD HYUNDAI OILBANK
- Address : 17-10, Mabuk-ro 240beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
- Emergency telephone number : 1588-5189

##### Supplier/Distributor information

- Company name : HD HYUNDAI OILBANK
- Address : 17-10, Mabuk-ro 240beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
- Emergency telephone number : 1588-5189

### 2. HAZARD IDENTIFICATION

#### A. GHS Classification

- Not applicable

#### B. GHS label elements

##### Hazard symbols

- Not applicable

##### Signal words

- Not applicable

##### Hazard statements

- Not applicable

##### Precautionary statements

###### 1) Prevention

- Not applicable

###### 2) Response

- Not applicable

###### 3) Storage

- Not applicable

4) Disposal

- Not applicable

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Distillates (petroleum), hydrotreated heavy paraffinic	Emulsifiable oil	64742-54-7	88 ~ 92
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Heavy paraffinic base lube stock ; Mineral oil, petroleum distillates, solvent dewaxed heavy paraffinic (severe solvent-refining and/or hydrotreatment) ; Solvent dewaxed heavy paraffinic distillate ; Adriatic spindle oil	64742-65-0	2 ~ 4
Distillates (petroleum), hydrotreated light paraffinic	Mineral oil, petroleum distillates, hydrotreated (severe) light paraffinic	64742-55-8	2 ~ 4
Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	Not available	85940-28-9	1 ~ 2
Distillates (petroleum), solvent-dewaxed light paraffinic	Solventdewaxed light paraffinic distillate (petroleum)	64742-56-9	~ 1
Distillates (petroleum), solvent-refined light paraffinic	CSR160805-21386	64741-89-5	~ 1
Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts ; Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts ; PHOSPHORODITHIOIC ACID, O,O-DI(C1-14)-ALKYL ESTERS ZINC SALT ; DI-C1-14 ALKYL DITHIOPHOSPHORIC ACID, ZINC SALT ; PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS,ZINC SALTS ; Dialkyl(C1-C14)dithiophosphoric acid, zinc salt ; Phosphorodithioic acid, O,O-di-C1-14-alkyl ester, zinc salt ; Zinc, O,O-di(C1-14)-alkylphosphorodithioate ;	68649-42-3	~ 1
Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)	CSR160805-41025	445409-27-8	~ 1
ar-Nonyl-N-(nonylphenyl)benzenamine	DINONYL DIPHENYLAMINE	36878-20-3	~ 1
Distillates (petroleum), hydrotreated heavy naphthenic	Hydrotreated heavy naphthenic distillates (petroleum) ; Severely solvent refined heavy paraffinic distillates ; Oils, mineral, heavy naphthenic, hydrotreated ; Oils, naphthenic, hydrogenated ; Mineral oil, petroleum distillates, hydrotreated (severe) heavy naphthenic ;	64742-52-5	~ 0.1

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.

#### C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.

#### D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.

#### E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

#### F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

### 5. FIREFIGHTING MEASURES

#### A. Suitable (Unsuitable) extinguishing media

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

#### B. Specific hazards arising from the chemical

- Not available

#### C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

### 6. ACCIDENTAL RELEASE MEASURES

#### A. Personal precautions, protective equipment and emergency procedures

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

#### B. Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

#### C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.
- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

### 7. HANDLING AND STORAGE

#### A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

#### B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.

- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### A. Exposure limits

#### ○ ACGIH TLV

- [Distillates (petroleum), hydrotreated heavy paraffinic] : TWA 5 mg/m<sup>3</sup>, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : TWA 5 mg/m<sup>3</sup>, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), hydrotreated light paraffinic] : TWA 5 mg/m<sup>3</sup>, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : TWA 5 mg/m<sup>3</sup>, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), solvent-refined light paraffinic] : TWA 5 mg/m<sup>3</sup>, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), hydrotreated heavy naphthenic] : TWA 5 mg/m<sup>3</sup>, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)

#### ○ OSHA PEL

- [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO<sub>3</sub>)] : 5 mg/m<sup>3</sup> (Soluble compounds), 15 mg/m<sup>3</sup> (Insoluble compounds - Total dust)

### B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

### C. Individual protection measures, such as personal protective equipment

#### ○ Respiratory protection

- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Consider warning properties before use.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- Respiratory protection is ranked in order from minimum to maximum.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.

#### ○ Eye protection

- Provide an emergency eye wash station and quick drench shower in the immediate work area.
- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.

#### ○ Hand protection

- Wear appropriate chemical resistant glove.

#### ○ Skin protection

- Wear appropriate chemical resistant protective clothing.

#### ○ Others

- Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	Amber

B. Odor	Mild
C. Odor threshold	No data available
D. pH	No data available
E. Melting point/Freezing point	No data available
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	≥ 220°C
H. Evaporation rate	No data available
I. Flammability(solid, gas)	No data available
J. Upper/Lower Flammability or explosive limits	No data available
K. Vapour pressure	No data available
L. Solubility	No data available
M. Vapour density	No data available
N. Specific gravity(Relative density)	0.864
O. Partition coefficient of n-octanol/water	No data available
P. Autoignition temperature	No data available
Q. Decomposition temperature	No data available
R. Viscosity	15.7cSt at 100°C
S. Molecular weight	No data available

## 10. STABILITY AND REACTIVITY

### A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

### B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

### C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.

### D. Incompatible materials

- Not available

### E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

## 11. TOXICOLOGICAL INFORMATION

### A. Information on the likely routes of exposure

- Respiratory tracts
  - Not available
- Oral
  - Not available
- Eye-Skin
  - Not available

### B. Delayed and immediate effects and also chronic effects from short and long term exposure

- Acute toxicity
  - \* Oral
    - Product (ATEmix) : >5000mg/kg
    - [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rat (Read-across CAS No. 64742-56-9) (OECD TG 401, GLP) (ECHA)

- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : LD50 > 5000 mg/kg Rat (IUCLID), LD50 > 5000 mg/kg Rat (Read-across 64742-56-9) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : LD50 > 5000 mg/kg Rat (Read across CAS No. 64742-56-9) (OECD TG 401, GLP) (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : Rat LD50=3080 mg/kg bw FHS 16CFR1500.3 OECD Guideline 401 GLP (ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : LD50 > 5000 mg/kg Rat (Read across CAS No. 64742-53-6) (OECD TG 401, GLP) (ECHA)
- [Distillates (petroleum), solvent-refined light paraffinic] : LD50 > 5000 mg/kg Rat (GLP, ECHA)
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : LD50 3100 mg/kg Rat (ECHA)
- [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)] : LD50 >5000 mg/kg Rat (OECD Guideline 401, GLP, ECHA)
- [Distillates (petroleum), hydrotreated heavy naphthenic] : LD50 > 5000 mg/kg Rat (IUCLID)

\* Dermal

- Product (ATEmix) : >5000mg/kg
- [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rabbit (Read-across CAS No. 64742-56-9) (OECD TG 402, GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : LD50 > 2000 mg/kg Rabbit (IUCLID), LD50 > 5000 mg/kg Rabbit (Read-across 64742-56-9) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : LD50 > 5000 mg/kg Rabbit (Read across CAS No. 64742-56-9) (OECD TG 402, GLP) (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : Rabbit LD50>20000mg/kg bw 16CFR1500.3 OECD Guideline 402 (ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : LD50 > 2000 mg/kg Rabbit (OECD TG 402, GLP) (ECHA)
- [Distillates (petroleum), solvent-refined light paraffinic] : LD50 > 5000 mg/kg Rabbit (GLP, ECHA)
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : LD50 > 3160 mg/kg Rabbit (ECHA)
- [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)] : LD50 >2000 mg/kg Rabbit (OECD Guideline 402, GLP, ECHA)
- [Distillates (petroleum), hydrotreated heavy naphthenic] : LD50 >5000 mg/kg Rabbit (IUCLID)

\* Inhalation

- Product (ATEmix) : 20.0mg/L < ATEmix <= 50.0mg/L, Vapour, 4hr
- [Distillates (petroleum), hydrotreated heavy paraffinic] : Aerosol LC50 > 5.53 mg/L 4 hr Rat (Read-across CAS No. 64741-88-4) (OECD TG 403) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Aerosol LC50 > 5.53 mg/L 4 hr, Rat (Read-across) (OECD TG 403) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : Aerosol LC50 2.18 mg/l 4 hr Rat (IUCLID)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : Aerosol LC50 2.18 mg/L 4 hr Rat (Read across CAS No. 64742-53-6) (OECD TG 403, GLP) (ECHA)
- [Distillates (petroleum), solvent-refined light paraffinic] : LC50 >5.53 mg/l 4 hr Rat (ECHA)
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : Vapour LC50 > 8.16 mg/L 6 hr (LC50 > 12.24 mg/L 4hr) Rat (ECHA)
- [Distillates (petroleum), hydrotreated heavy naphthenic] : Aerosol LC50 > 5.53 mg/L 4hr Rat No death Not classified (Read-across CAS No. 64741-88-4) (OECD TG 403) (ECHA)

Skin corrosion/irritation

- Not available

Serious eye damage/irritation

- Not available

Respiratory sensitization

- Not available

Skin sensitization

- Not available

- Carcinogenicity
  - \* IARC
    - Not available
  - \* OSHA
    - Not available
  - \* ACGIH
    - [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)] : A3\_Molybdenum (Soluble compounds)
  - \* NTP
    - Not available
  - \* EU CLP
    - [Distillates (petroleum), hydrotreated heavy paraffinic] : Carc. 1B (Note L)
    - [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Carc. 1B (Note L)
    - [Distillates (petroleum), hydrotreated light paraffinic] : Carc. 1B (Note L)
    - [Distillates (petroleum), solvent-dewaxed light paraffinic] : Carc. 1B (Note L)
    - [Distillates (petroleum), solvent-refined light paraffinic] : Carc. 1B (Note L)
    - [Distillates (petroleum), hydrotreated heavy naphthenic] : Carc. 1B (Note L)
- Germ cell mutagenicity
  - Not available
- Reproductive toxicity
  - Not available
- STOT-single exposure
  - Not available
- STOT-repeated exposure
  - Not available
- Aspiration hazard
  - Not available

## 12. ECOLOGICAL INFORMATION

### A. Ecotoxicity

- Fish
  - [Distillates (petroleum), hydrotreated heavy paraffinic] : LL50 > 100 mg/L 96 hr Pimephales promelas (Read-across) (OECD TG 203, GLP) (ECHA)
  - [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : LC50 5000 mg/l 96 hr Oncorhynchus mykiss (IUCLID), LL50 > 100 mg/L, 96hr, Pimephales promelas (Read-across) (ECHA)
  - [Distillates (petroleum), hydrotreated light paraffinic] : LC50 5000 mg/l 96 hr Oncorhynchus mykiss (IUCLID)
  - [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : LL50 4.5 mg/l 96 hr Oncorhynchus mykiss(OECD Guideline 203, GLP, Semi-static) (ECHA)
  - [Distillates (petroleum), solvent-dewaxed light paraffinic] : LC50 5000 mg/L 96 hr Oncorhynchus mykiss (IUCLID)
  - [Distillates (petroleum), solvent-refined light paraffinic] : LC50 5000 mg/l 96 hr Oncorhynchus mykiss (IUCLID)
  - [Distillates (petroleum), hydrotreated heavy naphthenic] : LL50 > 100 mg/L 96hr Pimephales promelas (Read-across IUPAC Name: Basestock solvent neutral 600) (OECD TG 203, GLP) (ECHA)
- Crustaceans
  - [Distillates (petroleum), hydrotreated heavy paraffinic] : EL50 > 10000 mg/L 48 hr Daphnia magna (Read-across), NOEL 10 mg/L 21 d Daphnia magna (Read-across 64742-53-6) (OECD TG 211, GLP) (ECHA) (ECHA)
  - [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : EC50 1000 mg/l 48 hr Daphnia magna (IUCLID), EL50 > 10000 mg/L 48 hr Daphnia magna (Read-across) (OECD TG 202), NOEL 10 mg/L 21 d Daphnia magna (Read-across 64742-53-6) (OECD TG 211, GLP) (ECHA)
  - [Distillates (petroleum), hydrotreated light paraffinic] : EC50 1000 mg/l 48 hr Daphnia magna (IUCLID)
  - [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : EC50 5.4 mg/l 48 hr

Daphnia magna(OECD Guideline 202, GLP, Static) (ECHA)

- [Distillates (petroleum), solvent-dewaxed light paraffinic] : EC50 1000 mg/L 48 hr Daphnia magna (IUCLID)
- [Distillates (petroleum), solvent-refined light paraffinic] : EC50 1000 mg/ℓ 48 hr Daphnia magna (IUCLID)
- [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)] : EC50 1.5 mg/ℓ 48 hr Daphnia magna (OECD Guideline 202, GLP, ECHA)
- [Distillates (petroleum), hydrotreated heavy naphthenic] : EL50 > 10000 mg/L 48hr, NOEL 10 mg/L 21d Daphnia magna (Read-across CAS No. 64742-53-6 or 64741-97-5) (OECD TG 202) (ECHA)

○ Algae

- [Distillates (petroleum), hydrotreated heavy paraffinic] : NOEL > 100 mg/L 72 hr (Read-across CAS No. 72623-87-1) (OECD TG 201) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : EC50 1000 mg/ℓ 96 hr Scenedesmus subspicatus (IUCLID), EC25 1152.9 mg/L 96hr, NOEL >= 100 mg/L 72hr Pseudokirchneriella subcapitata (Read-across 72623-87-1) (OECD TG 201) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : NOEL >= 100 mg/L Raphidocelis subcapitata 72 hr (Read across CAS No. 72623-87-1) (OECD TG 201) (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : ErC50 2.1 mg/ℓ 72 hr Selenastrum capricornutum(OECD Guideline 201, GLP, Static) (ECHA)
- [Distillates (petroleum), solvent-refined light paraffinic] : EC50 1000 mg/ℓ 96 hr Scenedesmus subspicatus (IUCLID)
- [Distillates (petroleum), hydrotreated heavy naphthenic] : NOEL >= 100 mg/L 72 hr Raphidocelis subcapitata (Read-across CAS No. 72623-87-1) (OECD TG 201) (ECHA)

## B. Persistence and degradability

○ Persistence

- [Distillates (petroleum), hydrotreated light paraffinic] : log Pow 1.99 ~ 18.02 (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : 8.87 qsar (ECHA)
- [Distillates (petroleum), solvent-refined light paraffinic] : log Kow 3.9 ~ 6 (IUCLID)
- [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)] : log Kow = 0.3 ~ 6.5 (ECHA)
- [Distillates (petroleum), hydrotreated heavy naphthenic] : log Pow 1.99 ~ 18.02 (20 °C, pH 7) (Calculated) (ECHA)

○ Degradability

- Not available

## C. Bioaccumulative potential

○ Bioaccumulative potential

- Not available

○ Biodegradation

- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not readily biodegradable, 31 % 28 d (O2 consumption) (Read-across) (OECD TG 301 F, GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Not readily biodegradable, 31 % 28 d (O2 consumption) (Read-across) (OECD TG 301 F, GLP) (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : 1.5 % 28 day
- [Distillates (petroleum), solvent-refined light paraffinic] : 6 (%) 28 day (Aerobic, Domestic wastewater, does not decompose easily)
- [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)] : 98 (%), 28 day (ECHA)
- [Distillates (petroleum), hydrotreated heavy naphthenic] : Not biodegradable, 31 % 28d (O2 consumption) (OECD TG 301F, GLP) (ECHA)

## D. Mobility in soil

- Not available

## E. Other adverse effects

- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : fish: NOEC(Fathead Minnow) >5000 mg/L/7days (IUCLID)
- [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : W/S : 1.268e-006 (EPISUITE) aquatic invertebrates, Daphnia magna, : NOErC, 21d, =0.8 mg/L, OECD Guideline 211, GLP, Flow-through

algae, Selenastrum capricornutum UTEX 1648, : ErC50, 96h, =2.1 mg/L, OECD Guideline 201, GLP, Static (ECHA)

- [Distillates (petroleum), solvent-refined light paraffinic] : fish: NOEC(Fathead Minnow) >5000 mg/L/7days

- [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)] : NOEC=0.47 mg/L, Algae(Scenedesmus subspicatus): 72h NOEC=0.625 mg/L (ECHA)

### 13. DISPOSAL CONSIDERATIONS

#### A. Disposal methods

- It shall be treated by incineration
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them
- Incinerate the oil by separating the oil and water
- The remainder of the water after separation will be processed in a water pollution prevention facilities.
- Do incineration or stabilization of the residue after disposal as the method of evaporation and concentration.
- Do incineration of the residue after disposal as the method of agglomeration and precipitation.
- Take care of incinerate or stabilization after treatment, purified by means of Separationdistillationextractiofiltrationpyrolysis

#### B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

### 14. TRANSPORT INFORMATION

#### A. UN No. (IMDG CODE/IATA DGR)

- Not applicable

#### B. Proper shipping name

- Not applicable

#### C. Hazard Class

- Not applicable

#### D. IMDG CODE/IATA DGR Packing group

- Not applicable

#### E. Marine pollutant

- Not applicable

#### F. Special precautions for user related to transport or transportation measures

- Air transport(IATA): Not subject to IATA regulations.
- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : Not available
- EmS SPILLAGE SCHEDULE : Not available

### 15. REGULATORY INFORMATION

#### A. National and/or international regulatory information

##### ○ POPs Management Law

- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not applicable
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Not applicable
- [Distillates (petroleum), hydrotreated light paraffinic] : Not applicable
- [Phosphorodithioic acid mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts] : Not applicable
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : Not applicable
- [Distillates (petroleum), solvent-refined light paraffinic] : Not applicable

- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : Not applicable
- [Amides, coco, N,N-bis(hydroxyethyl) reaction products with coco monoglycerides and molybdenum oxide(MoO3)] : Not applicable
- [ar-Nonyl-N-(nonylphenyl)benzenamine] : Not applicable
- [Distillates (petroleum), hydrotreated heavy naphthenic] : Not applicable

○ Information of EU Classification

\* Classification

- [Distillates (petroleum), hydrotreated heavy paraffinic] : H350
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : H350
- [Distillates (petroleum), hydrotreated light paraffinic] : H350
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : H350
- [Distillates (petroleum), solvent-refined light paraffinic] : H350
- [Distillates (petroleum), hydrotreated heavy naphthenic] : H350

○ U.S. Federal regulations

\* OSHA PROCESS SAFETY (29CFR1910.119)

- Not applicable

\* CERCLA Section 103 (40CFR302.4)

- Not applicable

\* EPCRA Section 302 (40CFR355.30)

- Not applicable

\* EPCRA Section 304 (40CFR355.40)

- Not applicable

\* EPCRA Section 313 (40CFR372.65)

- Not applicable

○ Rotterdam Convention listed ingredients

- Not applicable

○ Stockholm Convention listed ingredients

- Not applicable

○ Montreal Protocol listed ingredients

- Not applicable

## 16. OTHER INFORMATION

### A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

### B. Issue date

- 2023-03-15

### C. Revision number and Last date revised

- 1 times, 2025-06-19

### D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).