

SAFETY DATA SHEET

XTeer HD 3000 CF-4 10W-30 (ENG)

Date of issue: 2016-06-22

Revision date: 2025-08-07

Version: 2.1

1. IDENTIFICATION

A. Product name

- XTeer HD 3000 CF-4 10W-30 (ENG)

B. Recommended use and restriction on use

- General use: Automotive Engine oil
- Restriction on use: Do not use for purposes other than recommended.

C. Manufacturer / Supplier / Distributor information

Manufacturer information

- Company name: HD HYUNDAI OILBANK Co., Ltd
- Address: 477, Bundangsuseo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea
- Emergency telephone number: 1588-5189

Supplier/Distributor information

- Company name: HD HYUNDAI OILBANK Co., Ltd
- Address: 477, Bundangsuseo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea
- Emergency telephone number: 1588-5189

2. HAZARD IDENTIFICATION

A. GHS Classification

- Not applicable

B. GHS label elements

Hazard symbols

- Not applicable

Signal words

- Not applicable

Hazard statements

- Not applicable

Precautionary statements

1) Prevention

- Not applicable

2) Response

- Not applicable

3) Storage

- Not applicable

4) Disposal

- Not applicable

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Distillates (petroleum), hydrotreated heavy paraffinic	Emulsifiable oil	64742-54-7	87.0 ~ 93.0
Distillates (petroleum), hydrotreated light paraffinic	Mineral oil, petroleum distillates, hydro treated (severe) light paraffinic	64742-55-8	5.0 ~ 8.0
Polyethylenepolyamines reaction products with succinic anhydride polyisobutanyl derivs.	Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutanyl derivs.	84605-20-9	1.0 ~ 2.0
Calcium carbonate	Carbonic acid calcium salt (1:1) ; Calcite ; Limestone ; Marble ;	471-34-1	~ 1.0
Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts ; Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts ; PHOSPHORODITHIOIC ACID, O,O-DI(C1-14)-ALKYL ESTERS ZINC SALT ; DI-C1-14 ALKYL DITHIOPHOSPHORIC ACID, ZINC SALT ; PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS,ZINC SALTS ; Dialkyl(C1-C14)dithiophosphoric acid, zinc salt ; Phosphorodithioic acid, O,O-di-C1-14-alkyl ester, zinc salt ; Zinc, O,O-di(C1-14)-alkylphosphorodithioate ;	68649-42-3	~ 1.0
Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased	Dodecylphenol, calcium salt, overbased, sulfurized, carbonated	68784-26-9	~ 1.0
Benzenesulfonic acid monoalkyl(C=16-24) derivs., calcium salts	Not available	70024-69-0	~ 1.0
N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene	Not available	68411-46-1	~ 1.0

Distillates (petroleum), solvent-dewaxed light paraffinic	Solventdewaxed light paraffinic distillate (petroleum)	64742-56-9	~ 0.1
Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based	Not available	72623-87-1	~ 0.1

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.

C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.

- Keep unauthorized personnel out.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

B. Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.
- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.
- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

○ ACGIH TLV

- [Distillates (petroleum), hydrotreated heavy paraffinic] : TWA 5 mg/m³, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), hydrotreated light paraffinic] : TWA 5 mg/m³, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : TWA 5 mg/m³, Inhalable particulate matter(Mi

neral oil, Pure, highly and severely refined)

- OSHA PEL
- Not applicable

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

Respiratory protection

- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Consider warning properties before use.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- Respiratory protection is ranked in order from minimum to maximum.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.

Eye protection

- Provide an emergency eye wash station and quick drench shower in the immediate work area.
- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield

Hand protection

- Wear appropriate chemical resistant glove.

Skin protection

- Wear appropriate chemical resistant protective clothing.

Others

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	Clear brown
B. Odor	Mild
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	Not available
G. Flash point	> 220°C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Not available
K. Vapour pressure	Not available

L. Solubility	Not available
M. Vapour density	Not available
N. Specific gravity(Relative density)	0.872
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	11.63 cSt at 100°C
S. Molecular weight	Not available

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- Respiratory tracts**
 - Not available
- Oral**
 - Not available
- Eye-Skin**
 - Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

Acute toxicity

* Oral

- Product (ATEmix) : >5000mg/kg
- [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rat (Read-across CAS No. 64742-56-9) (OECD TG 401, GLP) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : LD50 > 5000 mg/kg Rat (Read across CAS No. 64742-56-9) (OECD TG 401, GLP) (ECHA)
- [Calcium carbonate] : LD50 > 2000 mg/kg Rat No death Not classified (OECD TG 420, GLP) (ECHA)

- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : LD50 3100 mg/kg Rat (ECHA)
- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : Rat LD50>5000 mg/kg bw OECD 401 GLP (ECHA)
- [N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene] : LD50 > 5000 mg/kg Rat (OECD TG 401) (ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : LD50 > 5000 mg/kg Rat (Read across CAS No. 64742-53-6) (OECD TG 401, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : LD50 >5000 mg/kg Rat (Read-across Cas No. 64742-56-9) (OECD TG 401, GLP) (ECHA)

*** Dermal**

- Product (ATEmix) : >5000mg/kg
- [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rabbit (Read-across CAS No. 64742-56-9) (OECD TG 402, GLP) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : LD50 > 5000 mg/kg Rabbit (Read across CAS No. 64742-56-9) (OECD TG 402, GLP) (ECHA)
- [Calcium carbonate] : LD50 > 2000 mg/kg Rat No death Not classified (OECD TG 402, GLP) (ECHA)
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : LD50 > 3160 mg/kg Rabbit (ECHA)
- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : Rabbit LD50>4000mg/kg bw no death OECD 402 GLP (ECHA)
- [N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene] : LD50 > 2000 mg/kg Rat (OECD TG 402) (ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : LD50 > 2000 mg/kg Rabbit (OECD TG 402, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : LD50 >5000 mg/kg Rabbit (Read-across Cas No. 64742-56-9)(OECD TG 402, GLP) (ECHA)

*** Inhalation**

- Product (ATEmix) : 10.0mg/L 4hr < ATEmix <= 20.0mg/L 4hr
- [Distillates (petroleum), hydrotreated heavy paraffinic] : Aerosol LC50 > 5.53 mg/L 4 hr Rat (Read-across CAS No. 64741-88-4) (OECD TG 403) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : Aerosol LC50 2.18 mg/l 4 hr Rat (IUCLID)
- [Calcium carbonate] : Aerosol LC50 > 3 mg/L 4 hr Rat No death Not classified (OECD TG 403, GLP) (ECHA)
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : Vapour LC50 > 8.16 mg/L 6 hr (LC50 > 1 2.24 mg/L 4hr) Rat (ECHA)
- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : Rat LC50>1.67 mg/L air /1hr (: 0.84 mg/L air/4hr) OECD 403 GLP no death (ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : Aerosol LC50 2.18 mg/L 4 hr Rat (Read across CAS No. 64742-53-6) (OECD TG 403, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : Dust/mist LC50 2.18 mg/L 4hr Rat (IUCLID, NITE)

Skin corrosion/irritation

- Not available

Serious eye damage/irritation

- Not available

Respiratory sensitization

- Not available

Skin sensitization

- Not available
- **Carcinogenicity**
 - * **IARC**
 - Not available
 - * **OSHA**
 - Not available
 - * **ACGIH**
 - Not available
 - * **NTP**
 - Not available
 - * **EU CLP**
 - [Distillates (petroleum), hydrotreated heavy paraffinic] : Carc. 1B (Note L)
 - [Distillates (petroleum), hydrotreated light paraffinic] : Carc. 1B (Note L)
 - [Distillates (petroleum), solvent-dewaxed light paraffinic] : Carc. 1B (Note L)
 - [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : Carc. 1B (Note L)
- **Germ cell mutagenicity**
 - Not available
- **Reproductive toxicity**
 - Not available
- **STOT-single exposure**
 - Not available
- **STOT-repeated exposure**
 - Not available
- **Aspiration hazard**
 - Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- **Fish**
 - [Distillates (petroleum), hydrotreated heavy paraffinic] : LL50 > 100 mg/L 96 hr Pimephales promelas (Read-across) (OECD TG 203, GLP) (ECHA)
 - [Distillates (petroleum), hydrotreated light paraffinic] : LC50 5000 mg/l 96 hr Oncorhynchus mykiss (IUCLID)
 - [Polyethylenepolyamines reaction products with succinic anhydride polyisobutenyl derivs.] : LC50 1000 mg/l 96 hr (OECD 203, GLP) (EPA HPVIS)
 - [Calcium carbonate] : LC50 > 100 % v/v saturated solution 96 hr Oncorhynchus mykiss (OECD TG 203, GLP) (ECHA)
 - [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : Pimephales promelas 96hr LL50>=1000 mg/L OECD 203 GLP (ECHA)
 - [N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene] : LC50 > 100 mg/L 96hr Danio rerio (OECD TG 203) (ECHA)
 - [Distillates (petroleum), solvent-dewaxed light paraffinic] : LC50 5000 mg/L 96 hr Oncorhynchus mykiss (IUCLID)
 - [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : LL50 > 100 mg/L 96 hr Pimephales promelas (OECD TG 203, GLP) (ECHA)

○ Crustaceans

- [Distillates (petroleum), hydrotreated heavy paraffinic] : EL50 > 10000 mg/L 48 hr Daphnia magna (Read-across), NOEL 10 mg/L 21 d Daphnia magna (Read-across 64742-53-6) (OECD TG 211, GLP) (ECHA) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : EC50 1000 mg/ℓ 48 hr Daphnia magna (IUCLID)
- [Polyethylenepolyamines reaction products with succinic anhydride polyisobutenyl derivs.] : LC50 1000 mg/ℓ 48 hr (GLP) (EPA HPVIS)
- [Calcium carbonate] : EC50 > 100 % v/v saturated solution 48 hr Daphnia magna (OECD TG 202, GLP) (ECHA)
- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : Daphnia magna 48hr EL50>1000 mg/L OECD 202 GLP (ECHA)
- [N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene] : EC50 51mg/L 48 hr Daphnia magna (OECD TG 202, GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : EC50 1000 mg/L 48 hr Daphnia magna (IUCLID)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : EL50 > 10000 mg/L 48 hr Daphnia magna (Read across CAS No. 64742-53-6, 64741-97-5) (OECD TG 202) NOEL 10 mg/L 21day Daphnia magna (Read across Cas No. 64742-53-6)(OECDTG 211,GLP)(ECHA)

○ Algae

- [Distillates (petroleum), hydrotreated heavy paraffinic] : NOEL > 100 mg/L 72 hr (Read-across CAS No. 72623-87-1) (OECD TG 201) (ECHA)
- [Distillates (petroleum), hydrotreated light paraffinic] : NOEL >= 100 mg/L Raphidocelis subcapitata 72 hr (Read across CAS No. 72623-87-1) (OECD TG 201) (ECHA)
- [Polyethylenepolyamines reaction products with succinic anhydride polyisobutenyl derivs.] : ErC50 510 mg/ℓ 96 hr (GLP) (EPA HPVIS)
- [Calcium carbonate] : EC50 > 14 mg/L 72 hr, NOEC 14 mg/L 72 hr Desmodesmus subspicatus (OECD TG 201, GLP) (ECHA)
- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : Selenastrum capricornutum 96hr EL50 >500 mg/L OECD 201 GLP (ECHA)
- [N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene] : EC50 > 100 mg/L 72 hr Desmodesmus subspicatus (OECD TG 201) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : NOEL ≥ 100 mg/L 72hr Raphidocelis subcapitata (Read across Cas No.72623-87-1)(OECD TG 201)(ECHA)

B. Persistence and degradability

○ Persistence

- [Distillates (petroleum), hydrotreated light paraffinic] : log Pow 1.99 ~ 18.02 (ECHA)
- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : log Kow 9.5 (ECHA)

○ Degradability

- Not available

C. Bioaccumulative potential

○ Bioaccumulative potential

- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : BCF=2.2
- [N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene] : BCF 411 L/kg 42d Read-across Cas No. 27177-41-9 (ECHA)

○ Biodegradation

- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not readily biodegradable, 31 % 28 d (O2 consu

mption) (Read-across) (OECD TG 301 F, GLP) (ECHA)

- [Polyethylenepolyamines reaction products with succinic anhydride polyisobutenyl derivs.] : 16 (%) 28 day (OECD 301B,US EPA)
- [Calcium carbonate] : Readily biodegradable, 90 % 28 d (CO₂ evolution) (OECD TG 301 B, GLP) (ECHA)
- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : 4.7-10.8%/28 days (ECHA)
- [N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene] : Non biodegradation, 0 % degradation (CO₂ evolution) (OECD TG 301 B, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : Not readily biodegradable, 31% degradation (O₂ consumption) 28day (Read across Other lubricant base oil (Solvent neutral 600 base oil; MRD -94-981))(OECD TG 301F,GLP)(ECHA)

D. Mobility in soil

- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : Koc 3615000000000 (Estimate)

E. Other adverse effects

- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : W/S : >= 0.082 mg/L (ECHA) Algae Selenastrum capricornutum 96hr NOELR=500 mg/L OECD 201 GLP (ECHA)

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- It shall be treated by incineration
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- Not applicable

B. Proper shipping name

- Not applicable

C. Hazard Class

- Not applicable

D. IMDG CODE/IATA DGR Packing group

- Not applicable

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Air transport(IATA): Not subject to IATA regulations.
- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE :Not available
- EmS SPILLAGE SCHEDULE :Not available

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ POPs Management Law

- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not applicable
- [Distillates (petroleum), hydrotreated light paraffinic] : Not applicable
- [Polyethylenepolyamines reaction products with succinic anhydride polyisobutenyl derivs.] : Not applicable
- [Calcium carbonate] : Not applicable
- [Phosphorodithioic acid O,O-dialkyl(C=1-14) esters zinc salts] : Not applicable
- [Dodecyl phenol, sulfurized, carbonates, calcium salts, overbased] : Not applicable
- [Benzenesulfonic acid monoalkyl(C=16-24) derivs., calcium salts] : Not applicable
- [N-Phenylbenzenamine reaction products with 2,4,4-trimethylpentene] : Not applicable
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : Not applicable
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : Not applicable

○ Information of EU Classification

* Classification

- [Distillates (petroleum), hydrotreated heavy paraffinic] : H350
- [Distillates (petroleum), hydrotreated light paraffinic] : H350
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : H350
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : H350

○ U.S. Federal regulations

* OSHA PROCESS SAFETY (29CFR1910.119)

- Not applicable

* CERCLA Section 103 (40CFR302.4)

- Not applicable

* EPCRA Section 302 (40CFR355.30)

- Not applicable

* EPCRA Section 304 (40CFR355.40)

- Not applicable

* EPCRA Section 313 (40CFR372.65)

- Not applicable

○ Rotterdam Convention listed ingredients

- Not applicable

Stockholm Convention listed ingredients

- Not applicable

Montreal Protocol listed ingredients

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESI S, NLM, SIDS, IPCS

B. Issue date

- 2016-06-22

C. Revision number and Last date revised

- 1 times, 2025-08-07

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).